

Conditioning Cream

Valve Cleaning & Maintenance



TECHCON™



Conditioning Cream

Conditioning cream protects delicate parts within rotary auger valves

Conditioning cream is primarily used in the maintenance of rotary auger valves, especially in solder paste applications. Clogging is minimized, within the feed paths, as the conditioning cream provides a lubricating effect within the valve, connections and tubing.

Conditioning cream should be used before start-up of any new equipment or after installation of new feed tubes or connectors or when the equipment will not be used for two hours or longer.

Technical and Safety data sheets available upon request.

Part Number	Size
7105XCON	10ml
7305XCON	30ml
TS60C-CON	177ml

For Sales & Support

Techcon Corporate Headquarters

10800 Valley View Street

Cypress, California, 90630, USA

Tel: 1-714-230-2398

E-mail: [OEMorders@okinternational.com](mailto: OEMorders@okinternational.com)

Key Features & Benefits

- Compatible with solder paste flux. Trace residues will not interfere with solder reflow
- Saves disassembly and cleaning time
- Protects rotary valves when not in use
- Can be used as demonstration fluid

Techcon European Corporate Office

Eagle Close, Chandler's Ford Industrial Estate,
Eastleigh, Hampshire, SO53 4NF, UK.

Tel: +44 2380 489 100

E-mail: [europe-orders@okinternational.com](mailto: europe-orders@okinternational.com)

Or visit www.techcon.com

171005-1200-CL